



Facts

General description

Part number	630005205
Part status	Active
Warranty	2 year

Certifications

General	CE, FCC, KCC, UL 61010-2-201
---------	------------------------------

Mechanical

Mechanical size	196 x 146 x 52mm
Mounting option	Panel Mount
Number of touches	1million finger touch operations
Touch type	Resistive
Cut-out size	186 x 136mm
Weight	0.7 kg
Housing material	Plastic (PC+ABS), Gray

Power

Input voltage	24 V DC (18 to 32 VDC)CE: The power supply must conformwith the requirements according to IEC 60950 and IEC 61558-2-4.UL and cUL: The power supplymust conformwith the requirements for class II power supplies.
Power consumption (max)	9.6W
Input fuse	Internal DC fuse

System

CPU	ARM9 400 MHz
RAM	128 MB
FLASH	256 MB, 200 MB free

Drivers

X2 base 7

7" HMI with iX runtime

800 × 480 pixel (16:9)
TFT-LCD touch screen
200 MB application memory
1 × Ethernet, 4 × serial, 1 × USB as standard
Operating temperature -10° to +50° C
CE, FCC, KCC, UL approvals

Display

Size diagonal	7" diagonal
Resolution	800x480 pixels
Backlight	LED Backlight
Backlight life time	20000 hours
Backlight brightness	400 cd/m2
Backlight dimming	Industrial Dimming
Display type	TFT-LCD with LED backlight

Communication serial

Number of serial ports	2 Port 9pin DSUB
Serial port 1	RS 232 (RTS/CTS)
Serial port 2	RS422/485
Serial port 3	RS 232
Serial port 4	RS 485

Ethernet communication

Number of ethernet ports	1
Ethernet port 1	1x10/100 Base-T (shielded RJ45)

Expansion interface

Expansion port	No
SD card	No
USB	1xUSB 2.0 400mA

Environmental

Operating temperature	-10°C to +50°C
Storage temperature	-20° to +60°C
Shock	15g, half-sine, 11ms according to IEC60068-2-27
Vibration	1g, according to IEC 60068-2-6, Test Fc
Sealing front	IP65
Sealing back	IP20
Humidity	5% – 85% non-condensed

ABB - COMLI Master (5.7.2)	LS Industrial System - Glofa (5.3.0)
ABB - COMLI Slave (4.11.0)	LS Industrial System - Master K (5.4.0)
ABB - TotalFlow (5.2.1)	Matsushita - MEWTOCOL-COM (5.9.2)
Allen Bradley - ControlLogix Ethernet IP (4.24.1)	Mitsubishi Electric - Alpha2 (5.7.0)
Allen Bradley - DF1 (5.8.0)	Mitsubishi Electric - A-series (C24) (5.6.0)
Allen Bradley - DH485 (4.6.2)	Mitsubishi Electric - A-series (CPU) (5.10.0)
Allen Bradley - MicroLogix Ethernet (5.6.0)	Mitsubishi Electric - A-series (E71) (5.4.0)
Allen Bradley - SLC5/PLC5 Ethernet (5.4.0)	Mitsubishi Electric - Freqrol FR-A PLC (5.8.2)
Altus - Alnet I (5.8.0)	Mitsubishi Electric - FX Series ADP/BD (5.10.0)
Animatics - SmartMotor (5.2.1)	Mitsubishi Electric - FX Series ENET (5.4.1)
Beckhoff - ADS (5.12.1)	Mitsubishi Electric - FX Series Serial (5.16.0)
Beckhoff - ADS Symbolic (4.7.0)	Mitsubishi Electric - MC Protocol (5.11.4)
Beijer Electronics - iX Demo (4.4.0)	Mitsubishi Electric - MR-J2/MR-J3-T MELSERVO (5.9.0)
Bernecker + Rainer - Mininet (5.6.0)	Mitsubishi Electric - QnA/Qnn Serial (5.10.0)
BoschRexroth - IndraDrive C (5.2.1)	Mitsubishi Electric - QnA/Qnn (C24) (5.5.0)
CAN - FreeCan (J1939/NMEA2000) (5.3.5)	Mitsubishi Electric - Q-Series Ethernet (E71) (5.5.0)
CAN - CANopen (5.4.0)	Modicon - Modbus Master (5.19.4)
CODESYS - ARTI v2.x, v3.x (4.8.0)	Modicon - Modbus Slave RTU/TCP (4.20.2)
CODESYS - SoftControl Direct Access (4.4.0)	NEMA0183 - NEMA 0183 (4.6.0)
Cognex - InSight (5.2.2)	Omron - Ethernet IP (4.3.3)
Control Techniques - Unidrive (5.3.1)	Omron - FINS (5.9.5)
CTC - Serial Binary (5.4.2)	Omron - Host Link (5.6.0)
Delta - PLC Modbus ASCII (5.6.0)	Regin - EXOline (5.3.2)
Emerson - Modbus Master RTU/ASCII (5.4.0)	Profibus - Profibus DP (5.5.1)
Eurotherm - Easy Serial 631 (5.1.1)	SAIA - S-BUS Serial/Ethernet (5.7.0)
Fatek - Facon (5.10.0)	Schneider Electric - Modbus (5.3.0)
Galil - DMC (5.2.2)	Schneider Electric - TSX Uni-Telway (4.5.3)
GE Fanuc - Ethernet SRTP (5.5.0)	Siemens - S5 PG/AS511 (5.4.0)
GE Fanuc - SNPX (5.6.1)	Siemens - S7 200 PPI (5.8.5)
Gidding & Lewis - Motion control (5.4.0)	Siemens - S7 over TCP (S7-200/300/400/1200/1500) (4.18.0)
IAI - Xsel (5.4.1)	Siemens - MPI (HMI Adapter) (5.7.0)
Idec - Computer Link (5.8.0)	Siemens - MPI (CiX) (5.3.0)
Johnson Control - JCONTROL (5.2.1)	WAGO - Modbus TCP (5.10.0)
KEB - COMBIVERT (5.4.0)	Vigor - M/VB-Series (5.6.0)
Keyence - KV-series (5.6.0)	Yamaha - VIP (5.2.1)
Koyo - DirectNET (5.5.0)	Yaskawa - Memobus Master (5.7.0)
Koyo - K Sequence (5.3.1)	Yokogawa - FA-M3 (5.6.0)
Lenze - LECOM A/B (5.6.0)	

BASIC JAPAN

Basic Japan Co., Ltd. Suginami Tokyo, Japan
Phone: 03-5335-7651
E-mail: mail@basicjp.com
URL: www.basicjp.com