

DuraMON Glass 32” Radar & ECDIS



32”Monitor

- 船舶アプリケーション向けIEC60945認証取得

- Radar/ECDIS 船級取得済み
- ワイドスクリーン型高品質ディスプレイ
- 長期供給可能
- VESA (150x280mm) 向け、
デスク・ウォール各種設置用ブラケット

- 航海用 RADAR CAT I・II・III に準拠
- タッチキーでのバックライト調光
- LEDバックライト 0~100%調光可能
- 貴社ロゴ・特注スペック等のカスタマイズ可能
- ブザー内蔵

仕様

DuraMON

Display sizes: 32" Wide Screen LCD (TFT)

Display properties:	Size – Active area (Aspect)	Luminance	Contrast	Resolution
	31,5" - 698 x 393 mm (16/9)	450 Cd/m ²	3000:1	1920 x 1080

View angle: View angle (L/R/T/B) (typical) 89°/89°

Materials: Front: Sea Water Resistant Aluminium w. black powder coating RAL 9005

Rear: Sea Water Resistant Aluminium w. black powder coating RAL 9005

Touch: PCAP multi touch (Optional)

Window: Anti-Reflection coated front glass

Protection: IP65 front – IP20 rear

DuraMON I/O

Video inputs: 1 x VGA
1 x DVI-D
1 x Display Port 1.2 or / HDMI 1.4a

Recommended resolution is 1920x1080

Generally all VESA compatible video modes are supported.

Special modes supported on request.

Control inputs: 1x RS232 – for remote control

1x RS-422/485 (Optional)

1x USB for touch sensor (Optional)

1x Built-in Buzzer (75-85 dB(A) / 1m)

DuraMON 電源

Standard: 90-264Vac. 50-60Hz Input

Optional: 18-31Vdc Input

Optional: Dual power, AC/DC (Optional)

DuraMON 環境

Operating Temperature: -15 to 55 °C

Storage Temperature: -25 to 70 °C

Relative Humidity: 8 to 95 %

DuraMON 適合規格

Marine: IACS E10 Rev. 6 & IEC 60945 Ed. 4

ECDIS: IEC 61174 ed. 4

Radar / Navigation: IEC 61174 ed. 4, IEC 62288 ed. 2, IEC 62388 ed. 2

Type Approvals: MR certificate

For latest marine class approvals – see www.isic-systems.com

DuraMON サイズ

Size: 762 (W) x 476 (H) x 77.7 (D)

Weight: 18 kg

Bracket: Desk / wall bracket - 150x280 VESA