

DuraMON Glass 55"



DuraMON シリーズは、船舶・軍事用途で極めて重要な航海計器情報の表示に適した設計のモニターです。

- 船級取得済み (Radar / ECDIS 含む)
- ワイドスクリーン型高品質ディスプレイ
- 長期供給可能
- VESA (400x350mm)
- マルチタッチオプション
- スプリットスクリーンレイアウト
- スリムデザイン
- 電動調整式チルトとリフトオプション
- 最大チルト角度 : 70 度
- 貴社ロゴ・特注スペック等のカスタマイズ可能

BASIC JAPAN

仕様

DuraMON

ディスプレイサイズ: 55" Wide Screen LCD (TFT)

ディスプレイ特性:

Size – Active area (Aspect)	Luminance	Contrast	Resolution
55" - 1210 x 680 mm (16/9)	450 Cd/m ²	4000:1	3840 x 2160
視野角:	View angle (L/R/T/B) (typical) 89°/89°		

材質: Front: Aluminium w. black power coating RAL 9005
Rear: Aluminium w. black power coating RAL 9005

タッチパネル: P-cap multi touch ※オプション

ウインドウパネル: Anti Reflection coated front glass

保護等級: IP65 front – IP20 rear

DuraMON I/O

ビデオ入力: 1 x VGA: Up to 1920x1080 60Hz
1 x DVI-D: Up to 1920x1080 60Hz
2 x Display Port 1.2a: Up to 3840x2160 (UHD) 60Hz
2 x HDMI 1.4: Up to 3840x2160 (UHD) 30Hz

Recommended resolution is 3840x2160.
Generally all VESA compatible video modes are supported.
Special modes supported on request.

制御: 1x RS-232 – for remote control.
1x USB for touch sensor (optional).
1x Tilt / Lift
1x External USB

DuraMON 電源

AC 電源仕様: 90-260VAC. 50-60Hz Input

DuraMON 仕様環境

動作時温度: -15 to 55 °C
保存時温度: -25 to 70 °C
相対湿度: 8 to 95 %

DuraMON 適合規格

船級: IACS E10 Rev. 6 & IEC 60945 Ed. 4
ECDIS: IEC 61174 ed. 4
Radar / Navigation: IEC 62288 ed. 2, IEC 62388 ed. 2
認証機関: Pending

For latest marine class approvals – see www.isic-systems.com

DuraMON アクセサリー

Wall mount
Electrical adjustable tilt and lift

DuraMON サイズ

Size: 1348,5 cm (W) 819,4 (H) 95 cm (D)

Weight: App. 65 kg