



## X2 pro 4 4" HMI with iX runtime

480 × 272 pixel (16:9)  
TFT-LCD touch screen  
1.5 GB application memory  
Ethernet 1x100 Mbit  
-10°C to +60°C operating temperature  
CE, FCC, KCC, UL approvals  
DNV, KR, GL, LR, ABS, CCS marine approvals

### Facts

#### General description

Part number	630000105
Part status	Active
Warranty	2 year

#### Certifications

General	CE, FCC, KCC, UL 61010-2-201
Marine	DNV, KR, GL, LR, ABS, CCS

#### Mechanical

Mechanical size	145 x 104 x 50mm
Mounting option	Panel Mount, VESA 50 x 50
Number of touches	1million finger touch operations
Touch type	Resistive
Cut-out size	130 x 89mm
Weight	0.5 kg
Housing material	Powder-coated aluminum, Gray

#### Power

Input voltage	24 V DC (18 to 32 VDC)CE: The power supply must conform with the requirements according to IEC 60950 and IEC 61558-2-4.UL and cUL: The power supply must conform with the requirements for class II power supplies.
Power consumption (max)	12W
Input fuse	Internal DC fuse

Power consumption (max)	12W
Input fuse	Internal DC fuse

#### System

CPU	i.MX6Solo Single Cortex-A9 1.0GHz 512kBL2cache
RAM	512 MB
FLASH	2GB SSD(eMMC), 1.5GB free for application

#### Display

Size diagonal	4.3" diagonal
Resolution	480x272 pixels
Backlight	LED Backlight
Backlight life time	50000 hours
Backlight brightness	300 cd/m2
Backlight dimming	Industrial Dimming
Display type	TFT-LCD with LED backlight

#### Communication serial

Number of serial ports	1 Port 9pin DSUB
Serial port 1	RS 232 (RTS/CTS)
Serial port 2	RS422/485
Serial port 3	RS485 (only if COM 2 is RS485)

#### Ethernet communication

Number of ethernet ports	1
Ethernet port 1	1x10/100 Base-T (shielded RJ45)

#### Expansion interface

Expansion port	Yes, ciX expansion module
SD card	SD and SDHC
USB	1xUSB 2.0 500mA

#### Environmental

Operating temperature	-10°C to +60°C
Storage temperature	-20°C to +70°C
Shock	15g, half-sine, 11ms according to IEC60068-2-27
Vibration	1g, according to IEC 60068-2-6, Test Fc
Sealing front	IP66, NEMA 4X/ 12 and UL Type 4X/ 12
Sealing back	IP20
Humidity	5% – 85% non-condensed

### Drivers

ABB - COMLI Master (5.7.2)  
ABB - COMLI Slave (4.11.0)  
ABB - TotalFlow (5.2.1)  
Allen Bradley - ControlLogix Ethernet IP (4.24.1)  
Allen Bradley - DF1 (5.8.0)  
Allen Bradley - DH485 (4.6.2)  
Allen Bradley - MicroLogix Ethernet (5.6.0)  
Allen Bradley - SLC5/PLC5 Ethernet (5.4.0)  
Altus - Alnet I (5.8.0)  
Animatics - SmartMotor (5.2.1)  
Beckhoff - ADS (5.12.1)  
Beckhoff - ADS Symbolic (4.7.0)  
Beijer Electronics - iX Demo (4.4.0)  
Bernecker + Rainer - Mininet (5.6.0)  
BoschRexroth - IndraDrive C (5.2.1)  
CAN - FreeCan (J1939/NMEA2000) (5.3.5)  
CAN - CANopen (5.4.0)  
CODESYS - ARTI v2.x, v3.x (4.8.0)  
CODESYS - SoftControl Direct Access (4.4.0)  
Cognex - InSight (5.2.2)  
Control Techniques - Unidrive (5.3.1)  
CTC - Serial Binary (5.4.2)  
Delta - PLC Modbus ASCII (5.6.0)  
Emerson - Modbus Master RTU/ASCII (5.4.0)  
Eurotherm - Easy Serial 631 (5.1.1)  
Fatek - Facon (5.10.0)  
Galil - DMC (5.2.2)  
GE Fanuc - Ethernet SRTP (5.5.0)  
GE Fanuc - SNPX (5.6.1)  
Gidding & Lewis - Motion control (5.4.0)  
IAI - Xsel (5.4.1)  
Idec - Computer Link (5.8.0)  
Johnson Control - JCONTROL (5.2.1)  
KEB - COMBIVERT (5.4.0)  
Keyence - KV-series (5.6.0)  
Koyo - DirectNET (5.5.0)  
Koyo - K Sequence (5.3.1)  
Lenze - LECOM A/B (5.6.0)

LS Industrial System - Glofa (5.3.0)  
LS Industrial System - Master K (5.4.0)  
Matsushita - MEWTOCOL-COM (5.9.2)  
Mitsubishi Electric - Alpha2 (5.7.0)  
Mitsubishi Electric - A-series (C24) (5.6.0)  
Mitsubishi Electric - A-series (CPU) (5.10.0)  
Mitsubishi Electric - A-series (E71) (5.4.0)  
Mitsubishi Electric - Freqrol FR-A PLC (5.8.2)  
Mitsubishi Electric - FX Series ADP/BD (5.10.0)  
Mitsubishi Electric - FX Series ENET (5.4.1)  
Mitsubishi Electric - FX Series Serial (5.16.0)  
Mitsubishi Electric - MC Protocol (5.11.4)  
Mitsubishi Electric - MR-J2/MR-J3-T MELSERVO (5.9.0)  
Mitsubishi Electric - QnA/Qnn Serial (5.10.0)  
Mitsubishi Electric - QnA/Qnn (C24) (5.5.0)  
Mitsubishi Electric - Q-Series Ethernet (E71) (5.5.0)  
Modicon - Modbus Master (5.19.4)  
Modicon - Modbus Slave RTU/TCP (4.20.2)  
NEMA0183 - NEMA 0183 (4.6.0)  
Omron - Ethernet IP (4.3.3)  
Omron - FINS (5.9.5)  
Omron - Host Link (5.6.0)  
Regin - EXOline (5.3.2)  
Profibus - Profibus DP (5.5.1)  
SAIA - S-BUS Serial/Ethernet (5.7.0)  
Schneider Electric - Modbus (5.3.0)  
Schneider Electric - TSX Uni-Telway (4.5.3)  
Siemens - S5 PG/AS511 (5.4.0)  
Siemens - S7 200 PPI (5.8.5)  
Siemens - S7 over TCP (S7-200/300/400/1200/1500) (4.18.0)  
Siemens - MPI (HMI Adapter) (5.7.0)  
Siemens - MPI (CiX) (5.3.0)  
WAGO - Modbus TCP (5.10.0)  
Vigor - M/VB-Series (5.6.0)  
Yamaha - VIP (5.2.1)  
Yaskawa - Memobus Master (5.7.0)  
Yokogawa - FA-M3 (5.6.0)

**BASIC JAPAN**

Basic Japan株式会社 Suginami Tokyo, Japan  
Phone: 03-5335-7651  
E-mail: mail@basicjp.com  
URL: www.basicjp.com